



bolt hole swivel castor with total brake d 100 mm series  
N2U6 roller bearing stainless steel

SKU: CJH36S0100N2U6Q0N

### Basic Specs

|                |        |
|----------------|--------|
| Load capacity  | 150 kg |
| Wheel Diameter | 100 mm |
| Tread Width    | 32 mm  |
| Total Height   | 126 mm |
| Unit Weight    | 0,6 kg |
| Swivel Radius  | 115 mm |

### Materials & Construction

|                       |  |
|-----------------------|--|
| Wheel Center Material | polyamide grey                         |
| Tread Material        | thermopl. polyurethane 95° shore A red |
| Wheel Hub Width       | 40 mm                                  |
| Bushing Diameter      | 12 mm                                  |

### Fastening & Mounting

|                         |           |
|-------------------------|-----------|
| Bolt size               | M8        |
| Fork Material Thickness | 02.00     |
| Fastening / Mounting    | bolt hole |
| Fastening Holes Spacing | 13        |
| Offset Dimension        | 36 mm     |
| Top Plate Thickness     | 02.50     |

**Additional Info**

|                    |                   |
|--------------------|-------------------|
| Temperature Range  | -40°C to +80°C    |
| SKU / Product Code | CJH36S0100N2U6Q0N |
| Series             | series N2U6       |
| DIN / EN Standard  | DIN EN 12532      |

**Bearings & Movement**

|                    |                                |
|--------------------|--------------------------------|
| Wheel Bearing Type | roller bearing stainless steel |
| Threadguard        | without separate threadguard   |