



swivel castor with total brake d 125 mm series N2U6 roller bearing

SKU: UCP35W0125N2U6R1W

Basic Specs

|                |         |
|----------------|---------|
| Load capacity  | 200 kg  |
| Wheel Diameter | 125 mm  |
| Tread Width    | 32 mm   |
| Total Height   | 155 mm  |
| Unit Weight    | 1,05 kg |
| Swivel Radius  | 127 mm  |

Materials & Construction

|                       |                                        |
|-----------------------|----------------------------------------|
| Wheel Center Material | polyamide grey                         |
| Tread Material        | thermopl. polyurethane 95° shore A red |
| Wheel Hub Width       | 50 mm                                  |
| Bushing Diameter      | 15 mm                                  |

Fastening & Mounting

|                            |              |
|----------------------------|--------------|
| Bolt size                  | M10          |
| Fork Material Thickness    | 02.50        |
| Fastening / Mounting       | plate        |
| Fastening Plate Dimensions | 105 x 80     |
| Fastening Holes Spacing    | 80 / 77 x 60 |
| Offset Dimension           | 45 mm        |
| Top Plate Thickness        | 02.50        |

Additional Info

|                    |                   |
|--------------------|-------------------|
| Temperature Range  | -40°C to +80°C    |
| SKU / Product Code | UCP35W0125N2U6R1W |
| Series             | series N2U6       |
| DIN / EN Standard  | DIN EN 12532      |

Bearings & Movement

|                    |                         |
|--------------------|-------------------------|
| Wheel Bearing Type | roller bearing          |
| Threadguard        | small metal threadguard |