



swivel castor with total brake d 160 mm series N2U6 roller bearing

SKU: UQP57W0160N2U6R1W

Basic Specs

| | |
|----------------|---------|
| Load capacity | 350 kg |
| Wheel Diameter | 160 mm |
| Tread Width | 40 mm |
| Total Height | 195 mm |
| Unit Weight | 2,28 kg |
| Swivel Radius | 165 mm |

Materials & Construction

| | |
|-----------------------|--|
| Wheel Center Material | polyamide grey |
| Tread Material | thermopl. polyurethane 95° shore A red |
| Wheel Hub Width | 59 mm |
| Bushing Diameter | 20 mm |

Fastening & Mounting

| | |
|----------------------------|---------------|
| Bolt size | M12 |
| Fork Material Thickness | 03.00 |
| Fastening / Mounting | plate |
| Fastening Plate Dimensions | 135 x 110 |
| Fastening Holes Spacing | 105 x 84 / 76 |
| Offset Dimension | 55 mm |
| Top Plate Thickness | 04.00 |

Additional Info

| | |
|--------------------|-------------------|
| Temperature Range | -40°C to +80°C |
| SKU / Product Code | UQP57W0160N2U6R1W |
| Series | series N2U6 |
| DIN / EN Standard | DIN EN 12532 |

Bearings & Movement

| | |
|--------------------|-------------------------|
| Wheel Bearing Type | roller bearing |
| Threadguard | small metal threadguard |